





> Antiperspirant Actives

ALOXICOLL[®] 31P

Standard Antiperspirant Active

INCI Name: Aluminumsesquichlorohydrate

Empirical Formula: Al₂(OH)_yCl_z x nH₂O (z=1,1-1,3, y=6-x)

Description

ALOXICOLL[®] 31P is a standard antiperspirant active. Its efficacy is due to the precipitation of basic Aluminium Chlorohydrate polymer complexes in the upper part of the sweat glands. These Aluminium Chlorohydrate polymers can be measured by HPLC. A typical HPLC trace for ALOXICOLL[®] 31P can be seen below, indicating the characteristic polymer distribution from band 1 to band 4.

Chemical Properties


ALOXICOLL[®] powders are stable under non aqueous conditions. Aqueous / alcoholic solutions of ALOXICOLL[®] are slightly acidic. At pH values > 5, insoluble Al(OH)₃ precipitates out. On drying, the residue decomposes to HCl and Al(OH)₃. On further heating, to temperatures >100°C, Al(OH)₃ releases water.

Physiological Properties

According to the application area and concentration applied, ALOXICOLL® exhibits sweat reducing, deodorant, astringent, antibacterial and antiphlogistic properties.

Application

ALOXICOLL® 31P is an antiperspirant active with a slightly higher efficacy over standard Aluminium Chlorohydrate, ALOXICOLL®L. It is primarily used in anhydrous formulations e.g. aerosols, sticks, soft solids, suspension roll-ons, powders and creams.




General Data

Form Aluminium Chloride Al : Cl Iron Heavy metals [as Pb] pH [15 % solution] Particle Size

fine powder 23,5 - 25,0% 17,5 - 19,0 % 1,7 - 1,8 max. 100 ppm max. 20 ppm 3,9 - 4,3 97 % < 45 μm 99,8 % < 106 μm

BK Giulini GmbH | A Member of the ICL Group



Raw Materials / Trade name	INCI name	w/w [%]
Gilugel [®] SIL 5 (1)	Cyclopentasiloxane (and) Cyclohexasiloxane (and) Aluminum/Magnesium Hydroxide Stearate	29,00
Isopropyl Myristate	Isopropyl Myristate	20,00
DC 345 Fluid(2)	Cyclopentasiloxane (and) Cyclohexasiloxane	18,00
Aloxicoll® 31P (1)	Aluminum Sesqui- chlorohydrate	33, 00
	Filling instruction:	
Antiperspirant bulk Propane Butane n-Pentane		25,00 5,25 29,75 40,00
D M C C C C C C C C C C		,
Raw Materials/ Trade name	INCI name	w/w [%]
	Cyclopentasiloxane (and) Cyclohexasilox- ane (and) Aluminum/Magnesium Hydroxide Stearate	-
Trade name A. Gilugel®	Cyclopentasiloxane (and) Cyclohexasilox- ane (and) Aluminum/Magnesium	[%]
Trade name A. Gilugel® SIL 5 (1)	Cyclopentasiloxane (and) Cyclohexasilox- ane (and) Aluminum/Magnesium Hydroxide Stearate Cyclopentasiloxane (and) Cyclohexasilox-	[%] 25,00
Trade name A. Gilugel® SIL 5 (1) DC 345 Fluid(2) Promyristyl	Cyclopentasiloxane (and) Cyclohexasilox- ane (and) Aluminum/Magnesium Hydroxide Stearate Cyclopentasiloxane (and) Cyclohexasilox- ane PPG-3 Myristyl	[%] 25,00 45,00
Trade name A. Gilugel® SIL 5 (1) DC 345 Fluid(2) Promyristyl PM-3 (3)	Cyclopentasiloxane (and) Cyclohexasilox- ane (and) Aluminum/Magnesium Hydroxide Stearate Cyclopentasiloxane (and) Cyclohexasilox- ane PPG-3 Myristyl Ether	[%] 25,00 45,00 5,00

Antiperspirant Aerosol A 68

Procedure

Mix **Gilugel**[®], IPM and volatile Silicone under rapid agitation.

Disperse the **Aloxicoll**[®] powder and mix under shear until the solids are uniformly dispersed. Add perfume, fill into cans, degas and pressurise.

Suppliers

BK Giulini
 Dow Corning

Antiperspirant Roll on A 69

Procedure

Combine **A** in a suitable vessel. Mix and homogenise until smooth and uniform. Add **Aloxicoll® 31P** slowly while stirring.

After completion of addition, homogenise again briefly.

Suppliers

1)BK Giulini 2)Dow Corning 3)Croda

Safety

ALOXICOLL[®] 31P is an Aluminium Sesquichlorohydrate according to USP 36. The FDA Final Antiperspirant Monograph classifies ALOXICOLL[®] types under category 1, as safe and effective for use in all types of antiperspirant formulations.

Packaging

ALOXICOLL® 31P powder is available in 80 kg PE drums.

Storage

ALOXICOLL[®] types can be stored for more than 3 years in original, unopened containers. Once opened, the powders should be used quickly and contact with moisture should be avoided. Storage of ALOXICOLL[®] 31P powder at high temperatures should be avoided.

BK Giulini GmbH has attempted to be accurate and informative regarding the products described herein: however, due to the vast potential for use of such products, we cannot take responsibility for results from the use of any product, method, or apparatus mentioned in this brochure. We must advise that no statement or suggestion herein is to be considered a recommendation or inducement for any use, manufacture, or sale that may infringe any patents now or hereafter in existence. It is the user's responsibility to make and be guided by his own tests in determining the suitability of any such product, method, or apparatus for any purpose.